

KNITTED AND WOVEN
FABRIC AUTOMATIC SPREADING MACHINE

针梭两用自动拉布机



功能特点 FEATURE

- ① 自动拨边装置 (解决针织布料卷边问题, 实现卷边拨平)
 - ② 自动伺服送布 (伺服自动跟随驱动送布滚轮的传动装置, 精准与主伺服行走相匹配, 实现无张力铺布效果, 对边精准度控制在5MM以内)
 - ③ 智能调节松紧装置 (当布架无布时, 自动完成原点归零、复位, 无需人工干预)
 - ④ 选配: 光电智能防撞装置 (可设定距离的光电感应防撞系统, 通过光电自动捕捉、识别工作过程中的障碍物, 提前自动停歇)
- Automatic edge smoothing device (Solve the edge curling problem of knitted, and achieve the curling edge smooth)
 - * Servo automatically follows the transmission device of driving cloth feeding roller, precisely matches with the main servo, perfectly realizes tension-free fabric spreading, intelligently automatically adjusts the tightness, and the edge to edge spreading accuracy is controlled within 5 mm*.
 - Intelligent adjustment elastic device (The machine will return back to original position once fabric finishing, no need manual intervention.)
 - Option: Photoelectric anti-collision device (Photoelectric anti-collision system with distance setting, automatically captures and recognizes obstacles during working by photoelectric, and automatically stops in advance)

适用于

SUITABLE FOR

常规的针织梭织布料。如: T恤、衬衫、童装、家居服、玩具、内衣、泳衣、棉衣、西裤、夹克、牛仔布等布料

General knitted and woven fabric. Such as: T-shirts, shirts, children's wear, home clothes, toys, underwear, swimwear, cotton wear, trousers, jackets, denim, etc.

技术参数

TECHNICAL SPECIFICATION

产品型号	Model	JY-160S	JY-190S	JY-210S	JY-260S	家纺 Home textile
有效工作宽度	Max. fabric width	1600mm	1900mm	2100mm	2600mm	可定制 Customized
最大布卷直径	Max. fabric roll diameter	500mm				
最大布卷重量	Max. fabric weight	80kgs				
最大驱动速度	Max drive speed	106m/min				
最大铺布高度	Max spreading fabric height	单位One-way 230mm/双拉Zigzag 160mm				
电源电压&功率	Voltage & Power	1 P AC 220V 50Hz 1Kw				
台板宽度	Request table width	1830mm	2130mm	2330mm	2830mm	可定制 Customized
机器尺寸 (长*宽*高)	Dimension (L*W*H)	190*230*125cm	190*260*125cm	190*280*125cm	190*330*125cm	可定制 Customized

机器可根据客户需求定做 Machine can be customized according to your requirements

WOVEN FABRIC
AUTOMATIC SPREADING MACHINE

梭织自动拉布机



功能特点 FEATURE

- ① 单拉压布装置 (针对较薄的梭织面料, 实现自动压布, 减少劳动强度, 提升铺布效率)
 - ② 自动伺服送布 (伺服自动跟随驱动送布滚轮的传动装置, 精准与主伺服行走相匹配, 实现无张力铺布效果, 对边精准度控制在5MM以内)
 - ③ 智能调节松紧装置 (当布架无布时, 自动完成原点归零、复位, 无需人工干预)
 - ④ 选配: 光电智能防撞装置 (可设定距离的光电感应防撞系统, 通过光电自动捕捉、识别工作过程中的障碍物, 提前自动停歇)
- One-way spreading press cloth device (for light and thin woven fabric, automatic pressing, reducing labor intensity and improving spreading efficiency)
 - * Servo automatically follows the transmission device of driving cloth feeding roller, precisely matches with the main servo, perfectly realizes tension-free fabric spreading, intelligently automatically adjusts the tightness, and the edge to edge spreading accuracy is controlled within 5 mm*.
 - Intelligent adjustment elastic device (The machine will return back to original position once fabric finishing, no need manual intervention.)
 - Option: Photoelectric anti-collision device (Photoelectric anti-collision system with distance setting, automatically captures and recognizes obstacles during working by photoelectric, and automatically stops in advance)

适用于

SUITABLE FOR

常见的梭织如: 涂层里布、西裤、夹克、牛仔布料。

General woven fabric. Such as: Coated cloth, trousers, jacket, denim.

技术参数

TECHNICAL SPECIFICATION

产品型号	Model	JY-160S3	JY-190S3
有效工作宽度	Max. fabric width	1600mm	1900mm
最大布卷直径	Max. fabric roll diameter	450mm	
最大布卷重量	Max. fabric weight	80kgs	
最大驱动速度	Max drive speed	106m/min	
最大铺布高度	Max spreading fabric height	单位One-way 230mm/双拉Zigzag 160mm	
电源电压&功率	Voltage & Power	1PH AC 220V 50Hz 1Kw	
台板宽度	Request table width	1830mm	2130mm
机器尺寸 (长*宽*高)	Dimension (L*W*H)	190*230*125cm	190*260*125cm

机器可根据客户需求定做 Machine can be customized according to your requirements