



COMMERCIAL LAUNDRY EQUIPMENT

JIANYE



Heating way 加热方式：
 Steam heating 蒸汽加热
 Electric heating 电加热

- Whole machine adapts the high quality stainless steel, which greatly extends the service life.
全不锈钢外表，美观大方，耐腐蚀性好。
- Large screen computer controller, flexible and professional, memory more than 40 sets of programs, at the same time with a manual operating system, in the case of failure of the computer controller can be switched to the emergency operating system, manual operation, complete the washing work.
采用大屏幕电脑版控制器，控制系统功能强，灵活专业，内存40多套程序，同时设有手动操作系统，在电脑控制器发生故障无法工作时，可切换至应急操作系统，手动操作，完成洗涤工作。
- Large diameter stainless steel door, inner drum using with high strength stainless steel, single side punching, double side polishing, reduce fabric wear.
大口径不锈钢门，内胆采用高强度优质不锈钢材料焊接而成，单面冲孔，双面抛光，减少了织物的磨损。
- Advanced inverter to control the motor speed, gentle startup, low noise and low energy consumption.
采用高性能变频驱动系统，无级变速，加速平顺，节能省电。
- Unique suspension shake-proof structure, low noise, high removal of excessive smooth washing, no foundation. (over 25kg using this structure)
悬浮减震结构，噪音低，洗涤高脱过度平稳，无需打地基。(25kg以上使用悬浮结构)
- Adopt shaft seat integrated structure, high quality bearing and durable.
采用轴座一体结构，高质量轴承经久耐用。

Technical Parameters:

Model		GXZ-15	GXZ-25	GXZ-50	GXZ-60	GXZ-100	GXZ-120
Capacity 容量	kg	15	25	50	60	100	120
Drum Size 洗衣缸尺寸	mm	Φ 700x350	Φ 800x500	Φ 980x650	Φ 1050x650	Φ 1200x850	Φ 1300x800
Washing Speed 洗涤速度	rpm	32	32	32	32	32	32
Extracting Speed 脱水速度	rpm	750	750	720	720	700	700
Motor Power 电机功率	kw	1.5	2.2	5.5	5.5	7.5	7.5
Water Consumption 耗水量	kg	192	240	560	720	944	1100
Electricity Heating Power 电加热功率	kw	12	18	28	28	40	40
Steam Consumption 耗蒸汽量	kg/kg	12	20	40	48	80	96
Net Weight 净重	kg	650	950	2000	2200	3000	3300
Overall Size 外形尺寸	mm	860x1120x1350	1100x1250x1550	1700x1455x1850	1760x1520x1900	1750x2000x2080	1790x2000x2100

Note: Then above specification are subject to change without notice.

注:以上规格如有更改，恕不另行通知。



Heating way 加热方式：

Steam heating 蒸汽加热 (GZZ)

Electric heating 电加热 (GDZ)

Gas heating 燃气加热 (GQZ)

- Using stainless steel as the inner drum to reduce fabric wear.
本系列工业烘干机的内胆采用优质不锈钢制造，降低织物的磨损。
- Optimized design of heat dissipation and fan, large size heater, fast heat exchange, high utilization of heat energy, fast heating, short drying time.
优化设计散热及风机，大规格加热器，热交换快，热能利用高，升温快，干衣时间短。
- The drum with high density ventilator ensures sufficient heat to pass through the linen, which can be fully dried in a short time.
滚筒高密度通风孔，确保充足的热量穿过布草，使布草在短的时间内得以充分烘干。
- The large-diameter loading and unloading door is used for convenient loading and unloading of clothes. The design of the doorway adopts the design of reverse overpass to avoid pulling the linen. The safety interlock ensures that the machine will stop running when the door is open.
采用大口径装卸门，装卸衣物方便，门口的设计采用反超口设计形式，避免拉扯布草。安全联锁装置确保大门打开状态下制动机器。
- Independent industrial computer control can precisely set the time and drying temperature of the dryer, computer controller with two touch button design, which is flexible and reliable in operation.
独立工控机控制可精确设定烘干机时间和烘干温度，电脑控制器采用两轻触式按键设计，操作灵活可靠。
- Large-area plush collection net, dust-proof net machine, adopts drawer-type structure, can be cleaned when pulled out, large-area through-hole rate ensures the smooth flow of the air duct, large-diameter fan blades are not easy to block the plush, and the equipment is simple to operate. High heat conversion efficiency.
大面积毛绒收集网，防尘网机，采用抽屉式结构，拉出即可清洁，大面积通孔率确保风道的畅通，大直径风叶，不容易堵塞毛绒，设备操作简单，热转换效率高。

Technical Parameters:

Model	GZ(D)(Q)Z-15	GZ(D)(Q)Z-25	GZ(D)(Q)Z-40	GZ(D)(Q)Z-50	GZ(D)(Q)Z-70	GZ(D)(Q)Z-100
Capacity 容量	15	25	40	50	70	100
Drum Size 滚筒尺寸	mm Φ 630x600	mm Φ 790x630	mm Φ 970x970	mm Φ 1050x970	mm Φ 1180x970	mm Φ 1400x1070
Motor Power 电机功率	kw 0.55	kw 0.75	kw 1.1	kw 1.1	kw 1.5	kw 2.2
Fan Power 风机功率	kw 0.55	kw 0.75	kw 1.1	kw 1.1	kw 1.5	kw 2.2
Electricity Heating Power 电加热功率	kw 14	kw 18	kw 21	kw 28	kw 32	kw 40
Steam Pressure 蒸汽压力	Mpa 0.2-0.6	Mpa 0.2-0.6	Mpa 0.2-0.6	Mpa 0.2-0.6	Mpa 0.2-0.6	Mpa 0.2-0.6
Steam Consumption 耗蒸汽量	kg/kg 16.5	kg/kg 27.5	kg/kg 44	kg/kg 55	kg/kg 80	kg/kg 110
Net Weight 净重	kg 380	kg 450	kg 550	kg 650	kg 720	kg 750
Overall Size 外形尺寸	mm 750x800x1500	mm 920x1050x1700	mm 1100x1450x2000	mm 1150x1500x2100	mm 1290x1750x2200	mm 1750x1530x2400

Note: Then above specification are subject to change without notice.

注:以上规格如有更改，恕不另行通知。

- Two doors design separate soiled and clean side for anti-contamination environment. (Perfect for clean room and healthcare laundry)
- Parts in contact with water made of SS304 stainless steel.
- Automatic door system Frequency inverter drive allows variable speed setting.
- Automatic computer control program, with full Chinese and English man-machine dialogue interface, easy to understand, easy to operate.
- Automatic start-stop temperature adjusting device improves thermal efficiency, temperature upper limit protection switch, soft start, more convenient for medical disinfection, temperature control.
- Standard cold and hot water inlet valves and one drain valve.
- Direct steam injection heating.
- Automatic brake stop function.
- Automatic soapbox compartments*3.
- Sight glass to view the inner drum.
- Heating way: steam heating.



隔离墙将洗衣房分成“洁净区”和“非洁净”区两个独立的操作区间。洗涤物由位于“非洁净区”一侧的装料门装入洗涤完毕后从位于“洁净区”一侧的卸料门取出，加上洁净空气控制系统的作用，可以防止细菌和尘埃颗粒从“非洁净区”流向“洁净区”，从而避免了洁净洗涤物的二次污染和交叉感染。

控制系统：前进后出，自动对门系统，电脑全自动控制程序，具有全中、英文人机对话界面，简单易懂，容易操作；自动刹车停机功能。

内胆材质：高强度不锈钢滚筒。

传动皮带：采用进口三角皮带。

控温装置：设有自动开停温度自动调节装置，提高热效率，温度上限保护开关，软启动，更加方便医用消毒，温度控制。

隔离式洗衣脱机广泛应用于医院、食品、生物制药、核电站等环境有严格无尘、无菌要求的洗衣房，是洗衣房的理想洗涤设备。

Technical Parameters:

Model		XGQ-50F	XGQ-100F	XGQ-120F
Capacity 容量	kg	50	100	120
Drum Diameter 滚筒尺寸	mm	Φ 800x1050	Φ 900x1470	Φ 1000x1500
Compartment 间隔	/	2	2	2
Motor Power 电机功率	kw	5.5	11	11
Inverter 变频功率	kw	7.5	15	15
Speed 速度	rpm	35-680	35-680	35-680
Steam Pressure 蒸汽压力	Mpa	0.4-0.8	0.4-0.8	0.4-0.8
Net Weight 净重	kg	1700	2300	2800
Overall Size 外形尺寸	mm	1900x1400x2050	2100x1850x2200	2200x1900x2300

Note: Then above specification are subject to change without notice.

注:以上规格如有更改，恕不另行通知。

Self-service Commercial Dryer (upper)

自助式全自动烘干机(上层)

- Stainless steel shell and liner, very beautiful, durable and rust free.
不锈钢外壳和内胆，高端大方，耐用不生锈。
- It is available to run in one-way direction and two-way direction.
有单向运行和双向运行两种方式。
- The forward and reverse operation turns to disperse the cloth and make the cloth softer.
正反转运行转动，打散布料，使布草更松软。
- The machine is with wool fiber clean system, with cool and hot air choice programs, This can ensure the ideal drying effect, special for high grade clothes.
冷热风选择程序尤其适用于烘干高档衣物布料。
- Heating models for choice: electric heating and gas heating.
有电加热或燃气形式。

Self-service Commercial Washer (Nether)

自助式全自动洗脱机（下层）

- Stainless steel shell and liner, very beautiful, durable and rust free.
不锈钢外壳和内胆，高端大方，耐用不生锈。
- Computer control, with automatic programs and manual programs for choice. The working condition can be displayed on the screen directly.
电脑板控制，具有中英文可选双语界面，显示系统当前运行信息。具有手动和自动二种控制方式，使得控制非常灵活方便。
- Washing and drying work can be done at the upper and nether machines together. Improve the working efficiency, save the space and labor.
洗涤和烘干工作可以在上部和下部机器一起完成。提高工作效率，节省空间和劳动力。
- The inner washing drum is designed with strong bearing structure to meet the high quality of washing and extracting need.
内胆设计成高强度支撑结构，保证高质量的洗涤和高速脱水所需的要求。
- About the washer, there are cold water and hot water inlets. There are cold water model and hot water model for order.
洗脱机提供冷水、热水2种加热形式。



Technical Parameters:

Model		XGQ-15M
Capacity 容量	kg	15/15
Washer Drum Size 洗涤滚筒尺寸	mm	Φ 670x340
Dryer Drum Size 烘干滚筒尺寸	mm	Φ 750x570
Washer Motor Power 洗涤电机功率	kw	1.5
Dryer Motor Power 烘干电机功率	kw	1.1
Net Weight 净重	kg	450
Overall Size 外形尺寸	mm	1000x950x2020

Note: Then above specification are subject to change without notice.
注:以上规格如有更改，恕不另行通知。



Technical Parameters:

Φ 500 ROLLER ELECTRIC HEATING (ONE-ROCCER)				
Model	YDI-1500	YDI-2000	YDI-2500	YDI-2800
Ironing Width 熨烫宽度 mm	1500	2000	2500	2800
Ironing Speed 熨烫速度 m/min	0-10	0-10	0-10	0-10
Roller Diameter 滚筒直径 mm	Φ 500	Φ 500	Φ 500	Φ 500
Max.Working Temp. 最高工作温度 °C	150	150	150	150
Motor Power 电机功率 kw	1.1	1.1	1.1	1.1
Heating Power 电加热功率 kw	16	18	20	28
Net Weight 净重 kg	850	900	1000	1200
Overall Size 外形尺寸 mm	1100x2200x1100	1100x2550x1100	1100x3200x1100	1100x3600x1100

Technical Parameters:

Φ 800 ROLLER						
Model	YDI-2800	YDII-2800	YZI-3000	YZII-3000	YZIII-3000	YZIV-3000
Ironing Width 熨烫宽度 mm	2800	2800	3000	3000	3000	3000
Roller Quantity 滚筒数量 /	1	2	1	2	3	4
Ironing Speed 熨烫速度 m/min	0-10	0-10	0-10	0-10	0-10	0-10
Roller Diameter 滚筒直径 mm	Φ 800	Φ 800	Φ 800	Φ 800	Φ 800	Φ 800
Max.Working Temp. 最高工作温度 °C	150	150	150	150	150	150
Motor Power 电机功率 kw	1.5	1.5	1.5	2.2	3	4
Heating Way 电加热功率 /	electric heating	electric heating	steam heating	steam heating	steam heating	steam heating
Net Weight 净重 kg	1300	2500	1550	3000	4200	5000
Overall Size 外形尺寸 mm	1360x3850x1330	2360x3850x1330	2360x4050x1330	2360x4050x1330	3360x4050x1330	4360x4050x1330

Note: Then above specification are subject to change without notice.
注:以上规格如有更改,恕不另行通知。



LAUNDRY AND MORE


JIANYE

JIANYE GROUP CO.,LTD.

- Industrial Washing
- Commercial Laundry
- Garment Process

Office Add: No.136, Shawan rd, Shawan, Panyu,
Guangzhou, China 511483
Tel: 86-20-3473 7881 FAX: 86-20-3473 7878

Website: www.jianyelaundry.cn
Email: jianye@jianyegroup.cn
helen@jianyegroup.cn
liz@jianyegroup.cn



Dynamic-Jianye FZE

**Official partner for
MIDDLE EAST**